

(19) World Intellectual Property  
Organization  
International Bureau



542631

(43) International Publication Date  
20 January 2005 (20.01.2005)


PCT

(10) International Publication Number  
**WO 2005/006070 A1**


- (51) International Patent Classification<sup>7</sup>: **G02F 1/139** (74) Agents: OKABE, Masao et al.; No. 602, Fuji Bldg., 2-3, Marunouchi 3-chome, Chiyoda-ku, Tokyo 1000005 (JP).
- (21) International Application Number: PCT/JP2004/009285
- (22) International Filing Date: 24 June 2004 (24.06.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 2003-194590 9 July 2003 (09.07.2003) JP
- (71) Applicant (for all designated States except US): CANON KABUSHIKI KAISHA [JP/JP]; 3-30-2, Shimomaruko, Ohta-ku, Tokyo 1468501 (JP).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): ASAO, Yasufumi [JP/JP]; c/o CANON KABUSHIKI KAISHA, 3-30-2, Shimomaruko, Ohta-ku, Tokyo 1468501 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: ECB-TYPE COLOUR LIQUID CRYSTAL DISPLAY WITH RESTRAINED TEMPERATURE DEPENDENCY OF COLOUR TONE



(57) Abstract: The present invention provides a liquid crystal display device (70) including a polarizing plate (87a, 87b), a pair of substrates (81a, 81b) at least one of which is transparent, a pair of electrodes (82a, 82b), and a nematic liquid crystal (85). The nematic liquid crystal is filled between the substrates, is aligned to be substantially perpendicular to the substrates when applying a voltage not higher than a threshold value between the electrodes, has negative dielectric constant anisotropy, and undergoes a change in tilt angle of alignment with respect to the substrates in accordance with applied voltage when applying a voltage not lower than a threshold value between the electrodes. The liquid crystal display device has a voltage range in which the rate of change in retardation level with respect to temperature is substantially zero, and displays red or purple when voltage is applied at the maximum voltage value in the voltage range. According to the present invention, changes in color tone depending on temperature are restrained.



**WO 2005/006070 A1**



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*